

New or Reconditioned	Model	Specifications
New	HSM100LH-1	1HP XP High Speed Dispenser, Air/Oil Hydraulic Lift, Table/Bench Mount Design, 2" Dispenser Blade operating at 10,000rpm, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, Inverter Duty 10:1 <u>TEFC</u> Motor.
New	HSM100LH-2	2HP XP High Speed Dispenser, Air/Oil Hydraulic Lift, Table/Bench Mount Design, 3.5" Dispenser Blade operating at 5700rpm, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, Inverter Duty 10:1 <u>TEFC</u> Motor.
New	HSD-5	5hp High Speed Dispenser, Lift Mounted on floor w/48" Rise, 6" Blade @ 8" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor.
New	HSD-7.5	7.5hp High Speed Dispenser, Lift Mounted on floor w/48" Rise, 8" Blade @ 8" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor.
New	HSD-10	10hp High Speed Dispenser, Lift Mounted on floor w/48" Rise, 10" Blade @ 8" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor.
New	HSD-15	15hp High Speed Dispenser, Lift Mounted on floor w/48" Rise, 12" Blade @ 8" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor.
New	HSD-20	20hp High Speed Dispenser, Lift Mounted on floor w/48" Rise, 14" Blade @ 8" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor.
New	HSD-25	25hp High Speed Dispenser, Lift Mounted on floor w/54" Rise, 16" Blade @ 8" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor.

New	HSD-30	30hp High Speed Disperser, Lift Mounted on floor w/54" Rise, 16" Blade @ 8" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor.
New	HSD-50	50hp High Speed Disperser, Lift Mounted on floor w/66" Rise, 18" Blade @ 12" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor. (Add \$910 for XP motor)
Reconditioned	HSD-5	5HP High Speed Disperser, Lift Mounted on floor w/48" Rise, 8" Blade @ 37" off floor, SS-304, Shaft Guard, Limit Switches, Adj. Can Lock, TEFC Motor. (OAH = 146.5" Raised, 98.5" lowered) With Mix Vessel, Atmospheric, 75-gal batch, 100-gal full holding, T304, 80-grit, dished bottom, 2" FBBV, outlet at 27" off the floor, 30psig @ 150f T304 jacket on sides, casters. Two piece loose fitting covers, T304, 80-grit.