

New or Reconditioned	Model	Specifications
New	VMC-2	Air/Oil Reverse Hydraulic Lift, Vac, SS304, 80grit in/out, 2-2" & 1- 1/2" ports, Viton, 1/2 HP TEFC 3-Wing Anchor, Viton lip seals, 1 HP TEFC M/E, 1 HP TEFC Disp, 10:1 speed ranges.
New	VMC-2	Air/Oil Reverse Hydraulic Lift, Vac, SS304, 80grit in/out, 2-2" & 1- 1/2" ports, Viton, 1/2 HP XP 3-Wing Anchor w/scrapers, Thermowell, Slings, Teflon lip seals, 1 HP TEFC M/E, 1 HP TEFC Disp, 10:1 speed ranges. Can to Cover clamps. Bench. MIX CAN VAC INT MACH 100PSIG SS JACKET 1" BALL VALVE CASTERS. CONTROLS NEMA 12 3/60/230V W/TEMP METER.
	VMC-40	SS-304, Vacuum, 2-3" S&G ports, 2-2" NPT ports, XP Thermowell, Butyl/Kalrez, Can-Cover Clamps, 50 psig CS jacket, 2" FBBV, Casters, 80 grit, 5HP anchor w/scrapers, 5HP ME slotted/Rulon, 7.5HP disperser, all motors XP all wired to Nema 7/9 Junction Box, 460v. TACS XP Nema 7/9, Start/Stop/Pot/E-Stop, Nema 12 VFD Panel 3/60/460v.
New	VMC-2	Air/Oil Reverse Hydraulic Lift, Vac, 5psig Int Pressure, SS304, 150grit in/out, 3-2" & 1- 1/2" ports, SS Light, Thermo, Silicon/Kalrez/Teflon, 1/2 HP XP 3-Wing Anchor, Fixed Scrapers, Teflon lip seals, Slings, 1 HP XP M/E, 1 HP XP Disp, 10:1 speed ranges. 100psig, 1" BV, Int Mach, Can-Cover clamps, casters. Vac Pump, 1/2HP TEFC, clear filter, gauge, valves, mounted in base. Nema 12 3/60/230v controls, dig temp, vac on/off, bench.
New	VMC-2	VMC-2 SPECIAL DESIGN. 2-1/2-GAL Full Holding, 2-Gal Batch. Air/Oil Reverse Hydraulic Lift, Vac, SS304, 150grit in/out, Two 2" & One 1/2"NPT ports, Thermo, Viton, 1/2 HP XP 3-Wing Anchor, Fixed Scrapers, Teflon lip seals, Slings, 1 HP XP M/E (SPECIAL SIZE), 1 HP XP Disp, 10:1 speed ranges. Mix Can, Special Tall 2-1/2-gal, 50psig, 1" BV, Int Mach, Can-Cover clamps. Nema 12 3/60/230v controls, dig temp, color chart recorder for torque and speed, bench w/leveling pads.

Reconditioned	VMC-10	SS-316, Vacuum, 5psig Internal, Raised Base 12", 1-3" ports, Push Button Lift, Sanitary XP light, 2 - 1/2"NPT ball valves (21" under valve), swing clamps, Kalrez, 50 psig SS ASME jacket, 2" FBBV tri-clamp, 1" SISAL w/Flush Plug, sanitary casters, thermo probe, 50-watt Tank Light, 150 grit int, 80-grit Ext, 3HP anchor w/scrapers, 1.5HP ME w/Super SLIM no bushing, 5HP disperser, all motors XP. NEMA 4X Control System Console with Touch screen PLC, 460V
Reconditioned	PVM-20S	Sanitary, 20gal VersaMix Multi-Agitator Processor, Vacuum, SS316, 150 grit, 15/11 hp vari-speed 3-wing agitator contoured to hemispherical vessel, Jordan Actuator, 2 speed XP 3/4 - 1-1/2 hp 6 bladed chopper (or disp blade), sanitary packing, lift provdies 67" under valve, 50 psig s/s jkt, 1-6" port, 1-3" port, Nema 7&9 controls. RENT @ \$4,800/month. For Pharm. Granulation.
Reconditioned	PVM-100	SS-304, 80-grit, VFD drive design, Vacuum, air/oil lift, 2-3" S&C port, Mechanical seals, Mix Can, vacuum design, 100PSIG @ 100f ASME carbon steel dimpled and insulated jacket, sheathed in s/s, 2" FBV w/ Tri Clover outlet, trunions, casters, 230/460 volt motors, 15HP XP High Speed Disperser, 10HP XP Anchor, 10HP XP HSM with slotted head and Teflon Bushing. Plus other extras available, controls available. Nema 12 VFD's 2-10HP 1-15HP 460v
Reconditioned	PVM-100	SS-304, 80-grit, VFD drive design, Vacuum, air/oil lift, 2-3" S&C port, Mechanical seals, Mix Can, vacuum design, 100PSIG @ 100f ASME carbon steel dimpled and insulated jacket, sheathed in s/s, 2" FBV w/ Tri Clover outlet, trunions, casters, 230/460 volt motors, 15HP XP High Speed Disperser, 10HP XP Anchor w/ scrapers, 10HP XP HSM with slotted head and Teflon Bushing.
Reconditioned	PVM-100	SS-304, 80-grit, ATMOSPHERIC NON-VACUUM DESIGN, DUAL SHAFT, air/oil lift, Viton, 1-4" vent port Loading Hopper 8x16, Mix Can (Non-CRS design) Non-Vacuum, Non-Jacketed 1-1/2" BV NPT off center, casters, 10HP XP HSD, 10HP XP Anchor w/fixed scrapers.

Reconditioned	VMC-100	SS-316, Vacuum, 2-7" ports w/wipers, 4 - 1", one 1/4", one 3/8" FNPT ports, pressure trans, 2" Tri-Clover, XP Tank Light, XP Thermowell (RTD), Swing Bolts, Viton, Kalrez in Mech Seals, 24" raised base, 50 psig CS jacket, 2" FBBV, Casters, 80 grit, 15HP anchor w/scrapers, 30HP ME slotted/Teflon, 30HP disperser 10" Blade w/10" Adj Blade, all motors XP all wired to Nema 12 Junction Box, 460V. Two mix vesels, each with 50 psi SS jackets, 3" FTBV, SS fork tubes. NEMA 4X console control system with speed, load indicators and electronic chart recorder.
New	CDA-2	SS-304, Vac, change-can (Std 2-gallon mix can), air/oil hyd lift, ss vac cover w/1/2" FNPT, 2-2" S&G ports, 100 psig ss jckt, 1" Ball Valve, Thermo, 80 grit in/out, mech seals, Viton, 2" Disp blade w/1HP TEFC motor, 2-Wing Anchor w/Scrapers & 1/2HP TEFC motor, Controls mounted and wired, Nema 12, VFD keypads w/start/stop/speed, raise/lower/safety controls, E-stop, Temp meter, disconnect, 230v, 3ph, 60Hz, Bench.
New	CDA-2	SS-316, Vac, Viton, change-can (Std 2-gallon mix can), air/oil hyd lift, ss vac cover w/1/2" FNPT, 2-2" S&G ports, 100 psig ss jckt, 1" Ball Valve, Int Mach, Thermo, 80 grit in/out, mech seals, shaft slingers & Teflon Lip Seals, Viton, 2" Disp blade w/1HP TEFC motor, 2-Wing Anchor w/Scrapers & 1/2HP TEFC motor, CS Bench w/leveling mounts.
New	CDA-10	SS-304, Vac, change-can, air/oil hyd lift, ss vac cover w/3/4" FNPT, 2-3" S&G ports, 15 psig cs jckt, 2" Ball Valve, Casters, 80 grit int, mech seals, Viton, 4" Disp blade w/5HP TEFC motor, 2-Wing Anchor w/3HP TEFC motor, 3/60/230/460v.
New	CDA-50	SS-316, Vac, change-can, air/oil hyd lift, ss vac cover w/1" FNPT, 2-3" S&G ports, 50 psig cs jckt, 2" Ball Valve, Casters, 150 grit int, mech seals, Viton, 7" Disp blade w/10HP TEFC motor, 2-Wing Anchor w/5HP TEFC motor, 3/60/230/460v. (TA) Select required controls.
New	CDA-100	SS-316, Vac, change-can, air/oil hyd lift, ss vac cover w/1" FNPT, 2-3" S&G ports, 50 psig cs jckt, 2" Ball Valve w/6" clearance, Casters, 150 grit int, mech seals, Viton, 8" Disp blade w/15HP TEFC motor, 2-Wing Anchor w/10HP TEFC motor, 3/60/230/460v.

	CDA-200	SS-304, Vac, change-can, air/oil hyd lift, ss vac cover w/1" FNPT, 2-3" S&G ports, 50 psig cs jckt (1.5"NPT ports), 2" Ball Valve (NPT) w/6" clearance, Casters, 80 grit int, mech seals, Viton, 12" Disp blade w/20HP TEFC motor, 2-Wing Anchor w/10HP TEFC motor, 3/60/230/460v.
New	CDA-200	SS-304, Vac, change-can, air/oil hyd lift, ss vac cover w/1" FNPT, 2-3" S&G ports, 50 psig cs jckt (1.5"NPT ports), 2" Ball Valve (NPT) w/6" clearance, Casters, 80 grit int, mech seals, Viton, 12" Disp blade w/20HP TEFC motor, 2-Wing Anchor w/10HP TEFC motor, 3/60/230/460v.
New	CDA-2	SS-316, Viton, Vac, change-can (Std 2-gallon mix can), air/oil hyd lift, ss vac cover w/1/2" FNPT, 2-2" S&G ports, Thermowell Type J, Mix Can, Int Mach, 100psig ss jckt, 1" Ball Valve, Casters, 80 grit in/out, mech seals, slingers, Teflon lip seals, 2" Disp blade w/1HP TEFC motor (1000-10,000rpm), 2-Wing Anchor w/Fixed Scrapers w/1/2HP TEFC motor, Controls mounted and wired, Two (2) 1HP Nema 1 VFD's 230v, 3ph, 60Hz, Bench.
	CDA-4	SS-316, Viton, 80-grit, Vac, change-can (Std 4-gallon mix can), air/oil hyd lift, ss vac cover three 3/4" FNPT, one 2" Tri S&G port w/metaglass, thermowell Type J, 100 psig ss jckt, Int Mach, 1" Ball Valve w/TC, casters, can-vac cover clamps, mech seals, 3" Disp blade w/2HP TEFC motor, 2-Wing Anchor w/Scrapers w/1HP TEFC motor, Controls mounted and wired, Nema 12, VFD keypads w/start/stop/speed, raise/lower/safety controls, E-stop, Temp meter, disconnect, 460v, 3ph, 60Hz.
Reconditioned	CDA-10	SS-304 80-grit, XP, Vacuum, 1-1" half coupling, Viton, Int Mach, 50psig CS jacket, 2" FBBV, 1" SISAL, Casters, 3HP anchor w/hinged scrapers, 5HP disperser. (CRS Built) (raised base) (TES/KALREZ, XP Thermo Probe, Nema 1 3HP & 5HP VFD's 230v)
Reconditioned	CDA-50	SS-316 80-grit, TEFC, ATMOSPHERIC, 1-2" port w/cover, Mix Can NON-JACKETED, Casters, 2" NPT FBBV, 5HP anchor, 10HP disperser.