

New or Reconditioned	Model	Description
New	42N-1S	3/4 hp motor, SS-316, Sanitary Design, center discharge, 36" off floor, 150-grit Ext, 150-grit Interior, 2" valve
New	42N-5	5 HP motor, SS-304, atmospheric, center discharge 36" off floor on legs, Single Cover with Safety Limit Switch, Shaft Guards, all SS 60-grit finish, 3" valve
New	42N-5S	5 HP motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Single Cover, SS-316 Split Stuffing Boxes, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. 3" valve
New	42N-5S	5 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Single Cover with Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. (3" Dust tight knife gate valve
New	42N-5SS	5 HP, TEFC motor, SS-316, (New) Sanitary Design, Atmospheric, ALL STAINLESS STEEL, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, 3" valve
New	42N-10	7.5 HP, TEFC motor, SS-304, atmospheric, center discharge 36" off floor, Teflon Braided Square Packing, Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. 4" Dust tight knife gate valve
New	42N-10	7.5 HP, TEFC motor, SS-304, atmospheric, center discharge 36" off floor, Teflon Braided Square Packing, Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. 4" Dust tight knife gate valve
New	42N-10S	7.5 HP, TEFC motor, SS-316, (New) Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.

New	42N-10S	7.5 HP, TEFC motor, SS-316, (New) Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
New	42N-10S	7.5 HP, TEFC motor, SS-316, (New) Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. (High HP Capable) (WITH 4" Dust tight knife gate valve
New	42N-10SS	7.5 HP, TEFC motor, SS-316, (New) Sanitary Design, Atmospheric, ALL STAINLESS STEEL, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
New	42I-10-P-SS	PADDLE AGITATOR, 7.5 HP, TEFC motor, SS-316, (New) Sanitary Design, Atmospheric WITH DUST TIGHT COVER CLAMPS, ALL STAINLESS STEEL, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. 4" Dust tight knife gate valve
New	42N-18	7.5 HP, TEFC motor, SS-304, atmospheric, 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, Aluminum Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 60-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. - 4" Dust tight knife gate valve
New	42N-18S	7.5 HP, TEFC motor, SS-316, Sanitary Design, 4" Dust tight knife gate valve, Atmospheric, with center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.

New	42N-18SS	7.5 HP, TEFC motor, SS-316, Sanitary Design, ALL STAINLESS STEEL, Atmospheric, with center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
New	42N-25	10 HP, TEFC motor, SS-304, atmospheric, 4" Dust tight knife gate valve Center Discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, Aluminum Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 80-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
New	42N-25S	10 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
New	42N-25S	10 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. (4" Dust tight knife gate valve)
New	42N-25SS	10 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, ALL STAINLESS STEEL, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
New	42N-36	20 hp, TEFC motor, s/s 304, atmospheric, center discharge 36" off floor, Teflon Braided Square Packing, neoprene, all SS 60-grit, c/s painted, 230/460 volt, 3 phase, 60 Hz. (High HP Capable) with 6" Dust tight knife gate valve.

New	42N-36S	20 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. with 6" Dust tight knife gate valve.
New	42N-36SS	20 HP, TEFC motor, SS-316, ALL STAINLESS STEEL, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish Int, 80-grit Ext, 230/460 volt, 3 phase, 60 Hz. (ADD VALVE AS REQUIRED).
New	42N-52	20 hp, TEFC motor, s/s 304, center discharge 36" clearance off floor, neoprene, all SS 80-grit, 230/460 volt, 3 phase, 60 Hz. ADD VALVE AS REQUIRED.
New	42N-52S	20 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. 8" Dust tight knife gate valve.
New	42N-62.5S	40 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. INCLUDES 8" DUST TIGHT KNIFE GATE.
New	42N-80	50 HP, TEFC motor, SS-304, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Three Piece Covers w/Safety Limit Switches, Teflon Braided Square Packing, SS-304 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, Interior 60-grit finish, 320-grit media blast exterior, c/s painted, 230/460 volt, 3 phase, 60 Hz.

New	42N-100S	50 HP, TEFC motor, SS-316, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, Three Piece Covers w/Safety Limit Switches, Teflon Braided Square Packing, SS-316 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. (10" Dust tight knife gate valve
New	42N-120	60 HP, TEFC motor, SS-304, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, three-piece cover with center stationary section, Safety Limit Switch, Teflon Braided Square Packing, SS-304 Split Stuffing Boxes, neoprene cover gasket, CS Shaft Guards, 60-grit Interior finish, 320-grit media blast exterior finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
New	42B-5	"B DESIGN" 3 HP, TEFC motor, SS-304, atmospheric, 70rpm, center discharge 36" off floor, Teflon Braided Square Packing, 1-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 3" KNIFE GATE VALVE
New	42B-10	"B DESIGN" 5 HP, TEFC motor, SS-304, atmospheric, 50rpm, center discharge 36" off floor, Teflon Braided Square Packing, 1-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 4" Knife gate valve (Nema 4, 5HP 460v VFD)
New	42B-18	"B DESIGN" 7.5 HP, TEFC motor, SS-304, 45rpm, atmospheric, center discharge 36" off floor, Teflon Braided Square Packing, 1-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 4" KNIFE GATE VALVE
New	42B-36	"B DESIGN" 15 HP, TEFC motor, SS-304, 40rpm, atmospheric, center discharge 36" off floor, Teflon Braided Square Packing, 2-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 6" KNIFE GATE VALVE

Reconditioned	42NSD-1S	3/4HP, TEFC/WASHDOWN motor, SS-316, 150-grit, Sanitary Design with bolted flanges, VACUUM DESIGN, 50psig SS jacket on Trough & Auger tube, RIBBON & PADDLE AGITATORS (80rpm), ribbon/paddle designed for center discharge, removable end wall scraper, low profile flush thermo type J, 2" dia Screw/Auger Discharge (1-13rpm) with 2-1/2" Tri-Clover flange outlet at bearing end of blender located 18" off floor, Nema 12 limit switch on discharge cap to prevent operation with cap in place, 1/3HP TEFC/WASHDOWN Screw/Auger motor, Teflon Braided Square Packing with air-purged latern rings, Vacuum cover with one 3" TC S&G port, one 6"TC Charge port, one 1/2"TC vac port, gas assist cylinders, FDA silicone gaskets, cover clamps, c/s painted supports, Nema 4X control panel 3/60/230V with 6" color touch screen display mounted and wired.
New	42B-1	"B DESIGN" 3/4 HP, TEFC motor, SS-304, atmospheric, 84rpm, center discharge 36" off floor, Teflon Braided Square Packing, 1-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 2" KNIFE GATE VALVE, Nema 12, 1/60/115v Input, 230v output VFD mounted & wired.
Reconditioned	42N-1S	3/4 hp, TEFC motor, SS-316, Sanitary Design, atmospheric, center discharge, 36" off floor, Teflon Braided Square Packing, neoprene, 150-grit Ext, 150-grit Interior, c/s painted, 230/460 volt, 3 phase, 60 Hz. (High HP Capable) - 2" Dust tight knife gate valve. Nema 4, 230v VFD mounted & wired.
Reconditioned	42N-1S	3/4 hp, TEFC motor, SS-304, Sanitary Design, atmospheric, 2" knife gate (Old Style) center discharge 36" off floor, Teflon Braided Square Packing, neoprene, 80-grit Ext, 150-grit Interior, c/s painted, 230/460 volt, 3 phase, 60 Hz. Nema 4 1HP 3/60/230v VFD mounted & wired. \$1610)
Reconditioned	42N-5P	PADDLE AGITATOR. 5 HP, TEFC motor, SS-304, atmospheric, 3" Dezurick knife gate valve mounted on 3" 150# ANSI flange, 36" off floor on legs, center discharge paddle agitator, Single Cover with Safety Limit Switch and cover clamps, Teflon Braided Square Packing, Aluminum Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 60-grit finish, c/s painted. 460 volt, 3 phase, 60 Hz. Nema 12 5HP VFD mounted & wired. Spray bar.

Reconditioned	42N-5S	5 HP, TEFC motor, SS-304, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, 3" Knife Gate Assembly, Single Cover with Safety Limit Switch, Teflon Braided Square Packing, SS-304 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz.
Reconditioned	42N-5S	5 HP, TEFC motor, SS-304, Sanitary Design, Atmospheric, center discharge 36" off floor on legs, 3" Knife Gate Assembly, Single Cover with Safety Limit Switch, Teflon Braided Square Packing, SS-304 Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 150-grit finish, c/s painted, 230/460 volt, 3 phase, 60 Hz. (5HP Nema 12 230v VFD w/Bracket - \$1547.00 #210220)
Reconditioned	42B-5	"B DESIGN" 3 HP, TEFC motor, SS-304, atmospheric, 70rpm, center discharge 36" off floor, Teflon Braided Square Packing, 1-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 3" KNIFE GATE VALVE
Reconditioned	42B-10	"B DESIGN" 5 HP, TEFC motor, SS-304, atmospheric, 50rpm, center discharge 36" off floor, Teflon Braided Square Packing, 1-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 4" KNIFE GATE VALVE (Nema 4, 5HP 460v VFD)
New	42B-18	"B DESIGN" 7.5 HP, TEFC motor, SS-304, 45rpm, atmospheric, center discharge 36" off floor, Teflon Braided Square Packing, 1-pc cover w/Neoprene Gasket, all SS 60-grit, 230/460 volt, 3 phase, 60 Hz. (Rated @ 35#/CF) 4" KNIFE GATE VALVE
Reconditioned	42N-25	20 HP, TEFC motor, SS-304, atmospheric, 4" Dust tight knife gate valve Center Discharge 36" off floor on legs, Safety Limit Switch, Teflon Braided Square Packing, Aluminum Split Stuffing Boxes, neoprene cover gasket, Shaft Guards, all SS 80-grit finish, c/s painted, VFD, 20HP Nema 12, 460 volt, 3 phase, 60 Hz.

Reconditioned	CVD-007	Cylindrical Vacuum Dryer, 7.5 cubic foot working, 9.6 cubic full holding, SS-304, 50psig @ 500F CS jacket, 3" roto-disc valve, thermo, 2 - 6" tri-clover port, 2 - 1"-150# couplings, Alum split stuffing boxes, 7.5HP XP INV Duty 10:1, 43rpm out, Paddle and Ribbon center discharge agitators, hollow shaft w/rotary union, 150-grit int, 2" fibreglass insulation, blast finish ext, Nema 4 VFD.
---------------	---------	--