

New or Reconditioned	Model	Specifications
New	VCB-010	10CF/280Liter, V-CONE TUMBLE BLENDER 15HP TEFC, 20-RPM, ATMOSPHERIC, SS-316, 240-GRIT INT FINISH, 150-GRIT EXT, 20RPM, SS-304 SUPPORT, 8" BUTTERFLY VALVE W/SILICON SEAT, 24" CLEARANCE UNDER VALVE, SAFETY RAILING WITH LIMIT SWITCH, 3/60/460V. 10CF/125#/CF MAX.
New	DCB-5	5CF/420Liter, DOUBLE CONE TUMBLE BLENDER WITH INTENSIFIER, 7.5HP TEFC, ATMOSPHERIC, SS-316, MIRROR INT FINISH, 150-GRIT EXT, 20RPM, SS-304 SUPPORT W/150-GRIT, 8" BUTTERFLY VALVE W/SILICON SEAT, VALVE HINGED W/QUICK CLAMP, 24" CLEARANCE UNDER VALVE, SAFETY RAILING WITH LIMIT SWITCH, 3/60/460V, CONTROLS INCLUDED.
New	VCB-025	25CF/700Liter, V-CONE TUMBLE BLENDER 10HP TEFC, 15-RPM, ATMOSPHERIC, SS-316, 240-GRIT INT FINISH, 150-GRIT EXT, 20RPM, SS-304 SUPPORT, 10" BUTTERFLY VALVE W/SILICON SEAT, 24" CLEARANCE UNDER VALVE, SAFETY RAILING WITH LIMIT SWITCH, 3/60/460V. 10CF/125#/CF MAX.
New	VCB-005	5CF/140Liter, V-CONE TUMBLE BLENDER 2HP TEFC MOTOR OPERATING AT 3-22RPM, ATMOSPHERIC, SS-316, MIRROR INT FINISH, 150-GRIT EXT, SS-304 SUPPORT W/150-GRIT, 6" BUTTERFLY VALVE W/SILICON SEAT, VALVE HINGED W/QUICK CLAMP, 35" CLEARANCE UNDER VALVE, SAFETY RAILING WITH LIMIT SWITCH, 3/60/460V, NEMA 4x Console Touchscreen PLC CONTROLS INCLUDED.
New	VCB-005	5CF/140Liter, V-CONE TUMBLE BLENDER, T316, 5HP TEFC MOTOR OPERATING AT 3-22RPM, ATMOSPHERIC, SS-316, 240-GRIT/MIRROR INT FINISH, 150-GRIT EXT, SS-304 SUPPORT W/150-GRIT, 6" BUTTERFLY VALVE W/SILICON SEAT, 24" CLEARANCE UNDER VALVE, SAFETY RAILING WITH LIMIT SWITCH, 3/60/230/460. 5CF/125#/CF MAX.